


B



B

A	PROCESS INLET ø2" PIPE FLANGE
B	PROCESS OUTLET ø1" PIPE FLANGE
C	AIR BLOW DOWN AND PUMP INLET ø1/2" NPT
D	HYDRAULIC SUPPLY AIR INLET ø3/8" NPT

NOTES:
1. DRAWING IS FOR REFERENCE ONLY. CONSULT FACTORY FOR DETAILED CONSTRUCTION DRAWINGS AND SPECIFICATIONS.
2. SEE FILTER PRESS SPECIFICATIONS SHEET FOR "X" DIMENSION.
3. PACIFIC PRESS RESERVES THE RIGHT TO MAKE CHANGES TO EQUIPMENT WITHOUT NOTICE.

CONFIGURATION APPROVAL
BY: _____
DATE: _____

PLATE SEALS

- ☐ EPDM (GASKETED) (STD)
- ☐ VITON (GASKETED)
- ☐ NON GASKETED

CLOTH TYPE

- ☐ PMU (STD)
- ☐ PMM
- ☐ FTW (POLYESTER)
- ☐ PSM

PLATE & PRESS PRESSURE RATING

- ☐ 100 PSI (STD)

CAKE THICKNESS

- ☐ 32mm (1.25") (STD)

PLATE SHIFTER

- ☐ NONE
- ☐ SEMI-AUTOMATIC

PUMP CONTROLS

- ☐ AP3P

MATERIAL HANDLING

- ☐ SLUDGE CART

FEED PUMP

- ☐ NONE
- ☐ PRESS MOUNTED

BLOWDOWN

PIPING MATERIAL

- ☐ PVC (STD)
- ☐ CPVC
- ☐ CARBON STEEL
- ☐ 304 S.S.
- ☐ 316 S.S. (TRICLOVER)

SEALS MATERIAL

- ☐ EPDM
- ☐ BUNA
- ☐ VITON
- ☐ TEFLO

MODEL # _____



Pacific Press Co.

Engineering Data

Nominal Volume		Number of Plates	Filter Area		"X" Dimension (")				Shipping Weight		Operating Weight	
					Gasketed (CGR)		Non-Gasketed (NGR)					
(ft ³)	(liters)		(ft ²)	(m ²)	(in)	(mm)	(in)	(mm)	(lb)	(kg)	(lb)	(kg)
3	85	13	76.4	7.1	29.625	752	30.13	765	1,935	878	2,175	987
4	113	15	89.2	8.3	34.125	867	34.63	879	1,935	878	2,255	1,023
5	142	19	114.7	10.7	43	1,092	43.75	1,111	2,047	929	2,447	1,110
6	170	23	140.1	13.0	52	1,321	52.88	1,343	2,159	979	2,639	1,197
8	227	29	178.4	16.6	65.5	1,664	66.50	1,689	2,327	1,056	2,967	1,346
10	283	35	216.6	20.1	78.875	2,003	80.25	2,038	2,495	1,132	3,295	1,495
12	340	43	267.5	24.9	96.75	2,457	98.38	2,499	2,663	1,208	3,623	1,643

Pacific Press reserves the right to change equipment specifications, options and pricing and/or discontinue models and options at any time without notice or obligation.

NOTES: Volume/Chamber = 0.29 ft³ (8.2 L)
 Filter Area/Chamber = 6.37 ft² (0.59 m²)
 Dimension and weights are for reference purposes only
 Weights do not include ancillary equipment
 For presses equipped with plate shifter add 200 lbs (182 kg)
 Operating weight is calculated with wet filter cake density of 85 lb/ft³ (1.36 kg/L)
 Cloth thickness on NGR based on 1mm/chamber
 * Filter plate stack length dimension (approximate)

P06L SIDEBAR

100 psi (7 bar) Design

PLATE TYPE

630mm CGR/NGR


CAKE THICKNESS

1.25" (32mm)


DWG NO

190006
SH2



REV
D



VIEW K-K



ISOMETRIC VIEW



Capacity (Cu Ft)	Qty Req'd on S/O		Total Weight (Lb)
	Small Cart A=50.00, B=24.00	Large Cart A=58.00 B=32.00	
4	1		300
5		1	350
6		1	350
8	*		*
10	2		600
12		2	700
* Use Next Higher Capacity Press w/ Extension Spacer			

CONFIGURATION APPROVAL
BY: _____
DATE: _____